

Safety Data Sheet

Printing date 01/13/2021

Revised On 04/29/21

1 Identification of the substance and manufacturer

Trade name:	TOUGH TRUCK COATING	TMC part number: 72234
Product code:	0000200041	
Recommended use:	Paint and coatings application.	
Uses advised against:	Any that differs from the recommended use.	
Manufacturer/Supplier:	Seymour of Sycamore 917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101 www.seymourpaint.com	Distributed by: The Maintenance Connection 31 Washington Avenue Scarborough, ME 04074 www.TheMaintenanceConnection.com Phone: (888)298-8585
Emergency telephone number:	1-800-255-3924	Emergency telephone number: 1-800-535-5053

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.
 Press. Gas H280 Contains gas under pressure; may explode if heated.
 Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2A H319 Causes serious eye irritation.
 Carc. 1B H350 May cause cancer.
 Repr. 2 H361 Suspected of damaging fertility or the unborn child.
 STOT SE 3 H336 May cause drowsiness or dizziness.
 STOT RE 2 H373 May cause damage to the central nervous system and the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

Additional information:
GHS Hazard pictograms

GHS02 GHS04 GHS07 GHS08

Signal word
Hazard statements

Danger
 Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 Causes skin irritation.
 Causes serious eye irritation.
 May cause cancer.
 Suspected of damaging fertility or the unborn child.
 May cause drowsiness or dizziness.
 May cause damage to the central nervous system and the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

Precautionary statements

Obtain special instructions before use.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Call a poison center/doctor if you feel unwell.
 Specific treatment (see on this label).
 Take off contaminated clothing and wash it before reuse.
 If eye irritation persists: Get medical advice/attention.
 Store in a well-ventilated place.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

Chemical Description	Concentration
74-98-6 propane	15-25%
67-64-1 Acetone	10-15%
8052-41-3 Stoddard Solvent	10-15%
106-97-8 n-butane	5-10%
110-19-0 Isobutyl Acetate	5-10%
110-54-3 hexane	≥5-<10%
108-65-6 PM acetate	1-5%
1330-20-7 xylene (mix)	1-5%

(Contd. on page 2)

Safety Data Sheet

Printing date 01/13/2021

Revised On 04/29/21

Trade name: TOUGH TRUCK COATING

(Contd. of page 1)

14807-96-6	Talc	1-5%
9006-04-6	Rubber	1-5%
1333-86-4	Carbon black	1-5%
64741-88-4	Paraffinic Petroleum oil	0.2-1%

4 First-aid measures

After inhalation:	Supply fresh air; consult doctor in case of complaints.
After skin contact:	Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact:	Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing:	Rinse mouth with water. Do not induce vomiting.
Most important symptoms and effects:	Dizziness
Indication of any immediate medical attention needed:	No further relevant information available.

5 Fire-fighting measures

Extinguishing agents:	CO ₂ , extinguishing powder or water spray. Fight larger fires with water spray.
Special hazards:	Can form explosive gas-air mixtures.
Protective equipment for firefighters:	A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Use respiratory protective device against the effects of fumes/dust/aerosol.
Methods and material for containment and cleaning up:	Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling	Use only in well ventilated areas.
Storage requirements:	Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection**Components with limit values that require monitoring at the workplace:****74-98-6 propane**

PEL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV (USA)	refer to Appendix F in TLVs&BEIs book; D, EX

67-64-1 Acetone

PEL (USA)	Long-term value: 2400 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 590 mg/m ³ , 250 ppm
TLV (USA)	Short-term value: 1187 mg/m ³ , 500 ppm Long-term value: 594 mg/m ³ , 250 ppm BEI

8052-41-3 Stoddard Solvent

PEL (USA)	Long-term value: 2900 mg/m ³ , 500 ppm
REL (USA)	Long-term value: 350 mg/m ³ Ceiling limit value: 1800* mg/m ³ *15-min
TLV (USA)	Long-term value: 525 mg/m ³ , 100 ppm

106-97-8 n-butane

REL (USA)	Long-term value: 1900 mg/m ³ , 800 ppm
TLV (USA)	Short-term value: 2370 mg/m ³ , 1000 ppm (EX)

110-19-0 Isobutyl Acetate

PEL (USA)	Long-term value: 700 mg/m ³ , 150 ppm
REL (USA)	Long-term value: 700 mg/m ³ , 150 ppm
TLV (USA)	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm

110-54-3 hexane

PEL (USA)	Long-term value: 1800 mg/m ³ , 500 ppm
-----------	---------------------------------------------------

(Contd. on page 3)

Safety Data Sheet

Printing date 01/13/2021

Revised On 04/29/21

Trade name: TOUGH TRUCK COATING

(Contd. of page 2)

REL (USA)	Long-term value: 180 mg/m ³ , 50 ppm
TLV (USA)	Long-term value: 176 mg/m ³ , 50 ppm Skin; BEI

108-65-6 PM acetate

WEEL (USA)	Long-term value: 50 ppm
------------	-------------------------

1330-20-7 xylene (mix)

PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV (USA)	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

9006-04-6 Rubber

TLV (USA)	Long-term value: 0.0001* mg/m ³ Skin; DSEN, RSEN,* inh. fraction
-----------	--------------------------------------------------------------------------------

1333-86-4 Carbon black

PEL (USA)	Long-term value: 3.5 mg/m ³
REL (USA)	Long-term value: 3.5* mg/m ³ *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
TLV (USA)	Long-term value: 3* mg/m ³ *inhalable fraction

Ingredients with biological limit values:**67-64-1 Acetone**

BEI (USA)	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----------	------------------------------------------------------------------------------------

110-54-3 hexane

BEI (USA)	0.4 mg/L Medium: urine Time: end of shift at end of workweek Parameter: 2,5-Hexanedione without hydrolysis
-----------	---------------------------------------------------------------------------------------------------------------------

1330-20-7 xylene (mix)

BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----------	----------------------------------------------------------------------------------------------

Hygienic protection:	Wash hands after use. Do not eat or drink while working.
Breathing equipment:	A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.
Hand protection:	Nitrile gloves. The glove material must be impermeable and resistant to the substance.
Eye protection:	Tightly sealed goggles

9 Physical and chemical properties

Appearance:	Aerosol.
Odor:	Aromatic
Odor threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range	Undetermined.
Boiling point:	-44 °C (-47.2 °F)
Flash point:	-19 °C (-2.2 °F)
Flammability (solid, gas):	Extremely flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor pressure:	Not determined.
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapor density	Not determined.
Evaporation rate	Not applicable.
Partition coefficient: n-octanol/water:	Not determined.

(Contd. on page 4)

Safety Data Sheet

Printing date 01/13/2021

Revised On 04/29/21

Trade name: TOUGH TRUCK COATING

(Contd. of page 3)

Solubility: Not determined.
Viscosity: Not determined.
Water: 0.0 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.
Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability: Not fully evaluated.
Possibility of hazardous reactions: No dangerous reactions known.
Incompatible materials: No further relevant information available.
Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information**LD/LC50 values that are relevant for classification:****110-19-0 Isobutyl Acetate**

Oral	LD50	4,763 mg/kg (rbt)
------	------	-------------------

108-65-6 PM acetate

Oral	LD50	8,500 mg/kg (rat)
------	------	-------------------

Inhalative	LC50/4 h	35.7 mg/l (rat)
------------	----------	-----------------

1330-20-7 xylene (mix)

Oral	LD50	8,700 mg/kg (rat)
------	------	-------------------

Dermal	LD50	2,000 mg/kg (rbt)
--------	------	-------------------

Inhalative	LC50/4 h	6,350 mg/l (rat)
------------	----------	------------------

1333-86-4 Carbon black

Oral	LD50	10,000 mg/kg (rat)
------	------	--------------------

Information on toxicological effects: No data available.
Skin effects: No irritant effect.
Eye effects: No irritating effect.
Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.
Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.
Other information: This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.
Bioaccumulative potential: No further relevant information available.
Mobility in soil: No further relevant information available.
Remark: Harmful to fish
Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950
DOT UN1950
DOT Aerosols, flammable
ADR 1950 Aerosols
Transport hazard class(es):
Class 2.1
Special precautions for user: Warning: Gases
EMS Number: F-D,S-U
Packaging Group: --
UN "Model Regulation": UN 1950 AEROSOLS, 2.1

15 Regulatory information**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

(Contd. on page 5)

Safety Data Sheet

Printing date 01/13/2021

Revised On 04/29/21

Trade name: TOUGH TRUCK COATING

(Contd. of page 4)

SARA Section 313 (Specific toxic chemical listings):

110-54-3	hexane
1330-20-7	xylene (mix)

Toxic Substances Control Act**(TSCA):**

All hazardous ingredients are found on the inventory list of substances.

Canadian Domestic Substances List**(DSL):**

All ingredients are listed or exempted.

Consumer Product Safety**Commission (CPSC):**

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

1333-86-4	Carbon black
100-41-4	ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

110-54-3	hexane
----------	--------

EPA:

67-64-1	Acetone	I
110-19-0	Isobutyl Acetate	D
110-54-3	hexane	II
1330-20-7	xylene (mix)	I

16 Other information

Contact:	Regulatory Affairs
-----------------	--------------------