

## SAFETY DATA SHEET

**PACER**  
**TECHNOLOGY**  
 INDUSTRIAL • PRIVATE LABEL



Date Prepared : 10/10/2014

MSDS No :

Date-Revised : 03/27/2015

Revision No : 8

## 1. PRODUCT AND COMPANY IDENTIFICATION

**GENERAL USE:** Cyanoacrylate adhesive product.

**PRODUCT DESCRIPTION:****MANUFACTURER**

Pacer Technology  
 3281 E. Guasti Rd., Suite 260  
 Ontario, CA 91761

**Emergency Contact:** CHEMTREC

**Emergency Phone:** 800-424-9300

**Alternate Emergency Phone:** 703-527-3887

**Product Stewardship:** 909-987-0550

TMC Part Numbers 73029, 73030

Distributed By

**The Maintenance Connection**

31 Washington Avenue  
 Scarborough, ME 04074  
 888-298-8585

## 2. HAZARDS IDENTIFICATION

**GHS CLASSIFICATIONS****Health:**

Eye Irritation, Category 2A

Skin Irritation, Category 2

Target Organ Toxicity (Single exposure), Category 3

Skin Sensitization, Category 1

**Physical:**

Flammable Liquids, Category 4

**GHS LABEL ELEMENTS**

Exclamation  
 mark

**SIGNAL WORD:** WARNING

**HAZARD STATEMENTS**

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H317: May cause an allergic skin reaction.

H335: May cause respiratory irritation.

H227: Combustible liquid.

**PRECAUTIONARY STATEMENT(S)****Prevention:**

P264: Wash skin and hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P271: Use only outdoors or in a well-ventilated area.

## SAFETY DATA SHEET



Date Prepared : 10/10/2014

MSDS No :

Date-Revised : 03/27/2015

Revision No : 8

P210: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

**Response:**

P370: In case of fire: Use dry chemical, foam or carbon dioxide to extinguish.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P313: Get medical advice/attention.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362: Take off contaminated clothing and wash before reuse.

P304+P340: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

**Storage:**

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P403+P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

**Disposal:**

7944L5O1: Dispose of in a manner consistent with federal, state, and local regulations.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
ETHYL-2-CYANOACRYLATE	85 - 100	7085-85-0
Polymethyl methacrylate	10 - 30	9011-14-7

### 4. FIRST AID MEASURES

**EYES:** Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

**SKIN:** Wash with soap and water. Peel or roll skin apart.

**INGESTION:** Peel or roll skin apart. Adhesive becomes solid in contact with saliva and may adhere to inside of mouth. Saliva will lift adhesive in 1-2 days. Avoid swallowing solid adhesive after detachment. Not a toxic product.

**INHALATION:** Remove to fresh air. Prolonged or repeated elevated exposure may cause allergic reactions with asthma-like symptoms in sensitive individuals.

**SIGNS AND SYMPTOMS OF OVEREXPOSURE**

**EYES:** Causes serious eye irritation. Will bond eyelids. Will cause excessive tearing.

**SKIN:** Bonds skin in seconds. May cause skin irritation. May cause sensitization by skin contact. Cyanoacrylates generate heat on polymerization, so very large amounts will burn the skin.

**INGESTION:** Adhesive becomes solid in contact with saliva and may adhere to inside of mouth. Saliva will lift adhesive in 1-2 days. Not a toxic product.

**INHALATION:** Prolonged or excessive inhalation may cause respiratory tract irritation.

**ACUTE TOXICITY:** Avoid exposure to vapor concentration in confined areas.

**CHRONIC EFFECTS:** Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis).

## SAFETY DATA SHEET



Date Prepared : 10/10/2014

MSDS No :

Date-Revised : 03/27/2015

Revision No : 8

## 5. FIRE FIGHTING MEASURES

**FLAMMABLE CLASS:** GHS Flammable liquid, Category 4**GENERAL HAZARD:** Combustible liquid and vapor. Product polymerized to solid by water.**EXTINGUISHING MEDIA:** Use dry chemical extinguisher or flush with large amounts of water.**FIRE FIGHTING EQUIPMENT:** As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.**HAZARDOUS DECOMPOSITION PRODUCTS:** Combustible by-products of carbon monoxide/dioxide.

## 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** Polymerize with water. Solid material may be scraped from surface.**LARGE SPILL:** Polymerize with water. Increase ventilation to area. Solid material may be scraped from surface.**ENVIRONMENTAL PRECAUTIONS****WATER SPILL:** None known.

## 7. HANDLING AND STORAGE

**GENERAL PROCEDURES:** Use with adequate ventilation. Avoid contact with eyes, skin and clothing.**HANDLING:** Avoid breathing (dust, vapor, mist, gas). Avoid contact with skin, eyes and clothing. Keep container closed when not in use.**STORAGE:** Store in a cool place in original container and protect from sunlight. Keep away from sources of ignition.**STORAGE TEMPERATURE:** Ideal storage: 41-50F (5-10C)**SHELF LIFE:** One year from the date of shipment from Pacer Technology, unless otherwise noted.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

## EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		Supplier OEL	
Chemical Name		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
ETHYL-2-CYANOACRYLATE	TWA	[1]	[1]	0.2	1.0	0.2 ppm	
<b>OSHA TABLE COMMENTS:</b>							
1. NL = Not Listed							

**ENGINEERING CONTROLS:** Use only in a well ventilated area. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.**PERSONAL PROTECTIVE EQUIPMENT****EYES AND FACE:** For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.**SKIN:** Use Nitrile gloves and aprons to prevent contact. Do not use PVC, Nylon or Cotton materials.

## SAFETY DATA SHEET



Date Prepared : 10/10/2014  
 MSDS No :  
 Date-Revised : 03/27/2015  
 Revision No : 8

**RESPIRATORY:** Use only in a well-ventilated area. In case of insufficient ventilation, wear suitable respiratory equipment.  
 Recommended: Full-face NIOSH-approved respirator with organic vapor cartridge.

**WORK HYGIENIC PRACTICES:** Avoid direct contact and breathing vapor. Use with adequate ventilation. Wash hands with soap and water after use.

**OTHER USE PRECAUTIONS:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**PHYSICAL STATE:** Liquid

**ODOR:** Characteristic odor, intensely irritating.

**ODOR THRESHOLD:** Odor Threshold = 1 ppm

**APPEARANCE:** Transparent, colorless thick liquid.

**pH:** Not Applicable.

**PERCENT VOLATILE:** Not Available

**FLASHPOINT AND METHOD:** 80°C (176°F) to 93.4°C (200°F) TAG CC

**FLAMMABLE LIMITS:** Not Available

**AUTOIGNITION TEMPERATURE:** 485°C (905°F)

**VAPOR PRESSURE:** < 0.2 mm Hg

**VAPOR DENSITY:** Not Available

**BOILING POINT:** > 149°C (300°F)

**FREEZING POINT:** Not Available

**MELTING POINT:** Not Determined

**THERMAL DECOMPOSITION:** Not Available

**SOLUBILITY IN WATER:** Insoluble

**EVAPORATION RATE:** Not Established

**DENSITY:** Not Available

**SPECIFIC GRAVITY:** 1.12 g/mL at 25°C

**VISCOSITY #1:** 20,000 to 50,000 Centipoise at 22°C (72°F)

**MOLECULAR WEIGHT:** Not Available

**(VOC):** < 20.000 g/L Per SCAQMD Method 316B.

**COEFF. OIL/WATER:** Partition coefficient (octanol/water): Not applicable.

## 10. STABILITY AND REACTIVITY

**STABLE:** Yes

**HAZARDOUS POLYMERIZATION:** No

**CONDITIONS TO AVOID:** Avoid temperatures above 176°F (80°C), moisture and alkalines.

**POSSIBILITY OF HAZARDOUS REACTIONS:** Possible polymerization reaction in the presence of water, amines, alkalis and alcohols.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon Dioxide, Carbon Monoxide and other toxic or irritating compounds may

## SAFETY DATA SHEET



Date Prepared : 10/10/2014  
 MSDS No :  
 Date-Revised : 03/27/2015  
 Revision No : 8

form when heated to decomposition. Oxides of nitrogen and probably hydrogen cyanide are also possible.

**INCOMPATIBLE MATERIALS:** Polymerized by water, alcohol, amines, alkaline materials.

**COMMENTS:** REACTIVITY: Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.

## 11. TOXICOLOGICAL INFORMATION

## ACUTE

Chemical Name	ORAL LD <sub>50</sub> (rat)	DERMAL LD <sub>50</sub> (rabbit)
ETHYL-2-CYANOACRYLATE	> 5000 mg/kg	> 2000 mg/kg

**DERMAL LD<sub>50</sub>:** > 2000 mg/kg

**Notes:** (Estimated)

**ORAL LD<sub>50</sub>:** > 5000 mg/kg

**Notes:** (Estimated)

**INHALATION LC<sub>50</sub>:** Vapors may be irritating. Recommended TWA 0.2ppm.

**EYE EFFECTS:** Bonds skin and eyes in seconds. Eye irritant.

**SKIN EFFECTS:** Irritating to skin. May cause allergic skin reaction with prolonged contact.

## CARCINOGENICITY

**IARC:** None known.

**NTP:** None known.

**OSHA:** None known.

**SENSITIZATION:** Possible skin sensitizer.

**TARGET ORGANS:**

<u>Ingredient</u>	<u>Health Effect/ Target Organ</u>
Ethyl cyanoacrylate	Irritant, Allergen/ Respiratory, Skin

## 12. ECOLOGICAL INFORMATION

**GENERAL COMMENTS:** None known.

## 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Dispose of following all Local Authority requirements for disposal.

## SAFETY DATA SHEET

**PACER**<sup>®</sup>  
**TECHNOLOGY**  
 INDUSTRIAL • PRIVATE LABEL



Date Prepared : 10/10/2014

MSDS No :

Date-Revised : 03/27/2015

Revision No : 8

## 14. TRANSPORT INFORMATION

## DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Not restricted

## ROAD AND RAIL (ADR/RID)

PROPER SHIPPING NAME: Not restricted

## AIR (ICAO/IATA)

SHIPPING NAME: Not regulated (less than 500 mL). AVIATION REGULATED LIQUID, N.O.S. (ETHYL CYANOACRYLATE), UN3334, 9.

## VESSEL (IMO/IMDG)

SHIPPING NAME: Not restricted

## CANADA TRANSPORT OF DANGEROUS GOODS

SHIPPING NAME: Not restricted

## 15. REGULATORY INFORMATION

## UNITED STATES

## SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Immediate Health, Delayed Health, Fire, Reactive.

313 REPORTABLE INGREDIENTS: None above reporting de minimus.

## 302/304 EMERGENCY PLANNING

EMERGENCY PLAN: None above reporting de minimus.

## TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
ETHYL-2-CYANOACRYLATE	7085-85-0
Polymethyl methacrylate	9011-14-7

TSCA STATUS: All components are listed on or are exempt from listing on the Toxic Substances Control Act.

## CLEAN AIR ACT

40 CFR PART 68---RISK MANAGEMENT FOR CHEMICAL ACCIDENT RELEASE PREVENTION: Not applicable.

CALIFORNIA PROPOSITION 65: No California Proposition 65 ingredients are known to be in this product.

## CANADA

## WHMIS HAZARD SYMBOL AND CLASSIFICATION

Combustible  
Liquid

Toxic

Class B3 - Combustible, D2B - Irritant.

## SAFETY DATA SHEET



Date Prepared : 10/10/2014

MSDS No :

Date-Revised : 03/27/2015

Revision No : 8

**WHMIS CLASS:** B3 - combustible, D2B - irritant.

**DOMESTIC SUBSTANCE LIST (INVENTORY):** All components are listed on or are exempt from listing on the Domestic Substances List.

## 16. OTHER INFORMATION


**PREPARED BY:** Mary Robles    **Date-Revised:** 03/27/2015

**REVISION SUMMARY:** This MSDS replaces the 10/21/2014 MSDS.

## HMIS RATING

HEALTH	<input type="checkbox"/>	2
FLAMMABILITY		2
PHYSICAL HAZARD		1
PERSONAL PROTECTION	<input type="checkbox"/>	

## NFPA CODES



## MANUFACTURER DISCLAIMER:

To the best of our knowledge, the information contained herein is accurate. However, Pacer Technology does not assume any liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.